

GSM4320XF

Preliminary Specification

40V N-Channel MOSFET

Absolute Maximum Ratings (T_A = 25°C unless otherwise specified)

Symbol	Parameter		Value	Unit
V _{DSS}	Drain-Source Voltage		40	V
V _{GSS}	Gate-Source Voltage		±20	V
I _D	Continuous Drain Current (Silicon Limited)	T _C =25°C	168	A
		T _C =100°C	106	
	Continuous Drain Current (Package Limited)		100	
I _{DM}	Pulsed Drain Current ¹		400	A
P _D	Power Dissipation	T _C =25°C	113	W
		T _C =100°C	45	
R _{θJC}	Thermal Resistance-Junction to Case		1.1	°C/W
R _{θJA}	Thermal Resistance-Junction to Ambient		62	°C/W
T _J	Operating Junction Temperature Range		-55 to +150	°C
T _{STG}	Storage Temperature Range		-55 to +150	°C



NOTE:

1. Single pulse width is limited by max junction temperature.

Electrical Characteristics (T_J = 25°C unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	40	-	-	V
I _{DSS}	Drain-Source Leakage Current	V _{DS} =40V, V _{GS} =0V	-	-	1	μA
I _{GSS}	Gate-Source Leakage Current	V _{DS} =0V, V _{GS} =±20V	-	-	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.2	-	2.5	V
R _{DS(ON)}	Drain-Source On-Resistance	V _{GS} =10V, I _D =20A	-	-	2	mΩ
		V _{GS} =4.5V, I _D =20A	-	-	3.4	
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _S =1A	-	-	1	V

Packages & Pin Assignments

DFN5X6-8L			Equivalent Circuit		
					
Pin	Symbol	Description	Pin	Symbol	Description
1	S	Source	8	D	Drain
2	S	Source	7	D	Drain
3	S	Source	6	D	Drain
4	G	Gate	5	D	Drain

NOTICE

- Globaltech Semiconductor assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Globaltech Semiconductor products described or contained herein. Globaltech Semiconductor products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Globaltech Semiconductor makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F, NO.43-1, Lane 11, Sec. 6, Minquan E. Rd Neihs District, Taipei City 114761, Taiwan (R.O.C).
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587