

# GSDSRB551V-30

## Schottky Barrier Diode


### Product Description

Schottky Barrier Diode 200mW / 30V


### Features

- Low Forward Voltage Drop
- Flat Lead SOD-323 Small Outline Plastic Package
- Surface Device Type Mounting
- RoHS Compliant
- Green EMC
- Matte Tin(Sn) Lead Finish
- Band Indicate Cathode

### Marking Information

Part Number	Package	Part Marking	Equivalent Circuit diagram
GSDSRB551V-30F	SOD-323	B3	

### Ordering Information



Part Number	Package	Quantity
GSDSRB551V-30F	SOD-323	3000 PCS

GSDSRB551V-30

## Absolute Maximum Ratings

( $T_A=25^\circ\text{C}$  Unless otherwise noted)

Symbol	Parameter	Value	Unit
$P_D$	Power Dissipation	200	mW
$V_{RM}$	Repetitive Peak Reverse Voltage	30	V
$V_R$	Maximum DC Blocking Voltage	20	V
$T_J$	Operating Junction Temperature	+125	$^\circ\text{C}$
$T_{STG}$	Storage Temperature Range	-65 to +125	$^\circ\text{C}$
$I_{F(AV)}$	Average Forward Rectified Current	500	mA
$I_{FSM}$	Peak Forward Surge Current (At 8.3ms Single half sine-wave)	5	A

These ratings are limiting values above which the serviceability of the diode may be impaired.


## Electrical Characteristics

( $T_A=25^\circ\text{C}$  Unless otherwise noted)


Symbol	Parameter	Test Condition	Min	Max	Unit
$B_V$	Breakdown Voltage	$I_R=500\mu\text{A}$	30	-	V
$I_R$	Reverse Leakage Current	$V_R=20\text{V}$	-	100	$\mu\text{A}$
$V_F$	Forward Voltage	$I_F=100\text{mA}$ $I_F=500\text{mA}$	-	0.36 0.47	V

## Typical Characteristics


Reverse Current vs Reverse Voltage



Total Capacitance




Forward Voltage vs Ambient Temperature



## Package Dimension

### SOD-323



#### NOTES:

1. The above package outline is similar to JEITA SC-90.
2. Dimensions are exclusive of Burrs, Mold Flash & Tie Bar extrusions.

Dimensions				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
<b>A</b>	1.6	1.8	0.063	0.071
<b>B</b>	1.15	1.35	0.045	0.053
<b>C</b>	0.8	1	0.031	0.039
<b>D</b>	0.25	0.4	0.01	0.016
<b>H</b>	0.05	0.25	0.002	0.01
<b>K</b>	2.3	2.7	0.091	0.106





Pin 1.CATHODE  
Pin 2.ANODE

## NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

## CONTACT US

### GS Headquarter

	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

### RD Division

	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587