

GSM02N15

150V N Channel MOSFET

Product Description

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode.

These devices are well suited for high efficiency fast switching applications.


Features


- 150V, 1.4A, $R_{DS(ON)} = 480m\Omega @ V_{GS} = 10V$
- Improved dv/dt capability
- TSOP-6 package design

Applications

- Portable Equipment
- Battery Powered System
- Load Switch


Packages & Pin Assignments

GSM02N15TSF (TSOP-6)		
		
Pin	Symbol	Description
1	D	Drain
2	D	Drain
3	G	Gate
4	S	Source
5	D	Drain
6	D	Drain




n-channel

Ordering Information



Part Number	Package	Quantity Reel
GSM02N15TSF	TSOP-6	3000 PCS

Marking Information



Absolute Maximum Ratings

T_A=25°C Unless otherwise noted

Symbol	Parameter	Typical	Unit
V _{DS}	Drain-Source Voltage	150	V
V _{GS}	Gate-Source Voltage	±20	V
I _D	Continuous Drain Current	T _C =25°C	1.4
		T _C =100°C	0.88
I _{DM}	Pulsed Drain Current (note 1)	5.6	A
P _D	Power Dissipation (T _C =25°C)	1.56	W
	Power Dissipation (Derate above 25°C)	0.012	W/°C
T _J	Operating Junction Temperature Range	-55 to +150	°C
T _{STG}	Storage Temperature Range	-55 to +150	°C
R _{θJA}	Thermal Resistance-Junction to Ambient	80	°C/W

Electrical Characteristics

($T_A=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	150			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2	3	4	V
I_{GSS}	Gate Leakage Current	$V_{DS}=0V, V_{GS}=\pm 20V$			± 100	nA
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=150, V_{GS}=0V$ $T_J=25^\circ\text{C}$			1	uA
		$V_{DS}=120V, V_{GS}=0V,$ $T_J=125^\circ\text{C}$			10	
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=10V, I_D=1A$		380	480	m Ω
		$V_{GS}=6V, I_D=0.5A$		410	520	
g_{FS}	Forward Transconductance	$V_{DS}=10V, I_D=1A$		1.7		S
V_{SD}	Diode Forward Voltage	$I_S=1.0A, V_{GS}=0V$ $T_J=25^\circ\text{C}$			1	V
Dynamic						
C_{iss}	Input Capacitance	$V_{DS}=25V,$ $V_{GS}=0V, f=1\text{MHz}$		350		pF
C_{oss}	Output Capacitance			34		
C_{rss}	Reverse Transfer Capacitance			26		
Q_g	Total Gate Charge (Note 2,3)	$V_{DS}=75V,$ $V_{GS}=10V, I_D=1.0A$		8.1		nC
Q_{gs}	Gate-Source Charge (Note 2,3)			2.0		
Q_{gd}	Gate-Drain Charge (Note 2,3)			2.7		
$t_{d(on)}$	Turn-On Time (Note 2,3)	$V_{DD}=75V,$ $R_G=10\Omega, I_D=1.0A,$ $V_{GS}=10V$		8.2		ns
T_r				5.8		
$t_{d(off)}$	Turn-Off Time (Note 2,3)			14.8		
T_f				8.0		

Note:

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed , pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
3. Essentially independent of operating temperature.

Typical Performance Characteristics




Fig.1 Continuous Drain Current vs. T_c




Fig.2 Continuous Drain Current vs. T_c




Fig.3 Normalized V_{th} vs. T_j




Fig.4 Gate Charge Waveform




Fig.5 Normalized Transient Impedance








Fig.6 Maximum Safe Operation Area



Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching Test Circuit & Waveforms



Package Dimension

TSOP-6









Dimensions				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	-	1.45	-	0.057
A1	0.00	0.10	0.000	0.004
A2	0.70	1.35	0.028	0.053
c	0.12 (REF)		0.005 (REF)	
D	2.70	3.10	0.106	0.122
E	2.60	3.00	0.102	0.118
E1	1.40	1.80	0.055	0.071
L	0.45 (REF)		0.018 (REF)	
L1	0.60 (REF)		0.024 (REF)	
θ	0°	10°	0°	10°
b	0.30	0.50	0.012	0.020
e	0.95 (REF)		0.037 (REF)	
e1	1.90 (REF)		0.075 (REF)	

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587