

GSM0959D

100V P-Channel MOSFET

Product Description

These P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode.

These devices are well suited for high efficiency fast switching applications.



Features

- -100V, -30A, $R_{DS(ON)}=45m\Omega@V_{GS} = -10V$
- Fast switching
- Green Device Available
- Improved dv/dt capability
- 100% EAS Guaranteed


Applications

- Networking
- Load Switch
- LED applications

Packages & Pin Assignments


GSM0959DF (TO-252-2L)		
 <p>Top View</p>		
Description		
Gate		
Drain		
Source		

Ordering Information



Part Number	Package	Quantity
GSM0959DF	TO-252-2L	2500pcs

Marking Information



Absolute Maximum Ratings

$T_C=25^\circ\text{C}$ Unless otherwise noted

Symbol	Parameter	Typical	Unit
V_{DS}	Drain-Source Voltage	-100	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Continuous Drain Current	$T_C=25^\circ\text{C}$	-30
		$T_C=100^\circ\text{C}$	-19
I_{DM}	Pulsed Drain Current ¹	-120	A
EAS	Single Pulse Avalanche Energy ²	180	mJ
IAS	Single Pulse Avalanche Current ²	-60	A
P_D	Power Dissipation ($T_C=25^\circ\text{C}$)	102	W
	Power Dissipation-Derate above 25°C	0.82	W/ $^\circ\text{C}$
T_J	Operating Junction Temperature Range	-55 to +150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to +150	$^\circ\text{C}$
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient	62	$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance-Junction to Case	1.22	$^\circ\text{C}/\text{W}$

Electrical Characteristics

T_J=25°C Unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250uA	-100			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250uA	-1.2	-1.6	-2.5	V
I _{GSS}	Gate-Source Leakage Current	V _{DS} =0V, V _{GS} =±20V			±100	nA
I _{DSS}	Drain-Source Leakage Current	V _{DS} =-100V, V _{GS} =0V			-1	uA
		V _{DS} =-80V, V _{GS} =0V T _J =85°C			-10	
I _S	Continuous Source Current	V _G =V _D =0V, Force Current			-30	A
I _{SM}	Pulsed Source Current				-60	A
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} =-10V, I _D =-15A		36	45	mΩ
		V _{GS} =-4.5V, I _D =-10A		40	55	
g _{FS}	Forward Transconductance	V _{DS} =-10V, I _D =-5A		22		S
V _{SD}	Diode Forward Voltage	I _S =-1A, V _{GS} =0V			-1	V

Electrical Characteristics (Continue)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Dynamic						
Q _g	Total Gate Charge ^{3,4}	V _{DS} =-50V, V _{GS} =-10V, I _D =-10A		98	150	nC
Q _{gs}	Gate-Source Charge ^{3,4}			16.2	30	
Q _{gd}	Gate-Drain Charge ^{3,4}			13.8	26	
C _{iss}	Input Capacitance	V _{DS} =-25V, V _{GS} =0V, f=1MHz		6315	9000	pF
C _{oss}	Output Capacitance			220	330	
C _{rss}	Reverse Transfer Capacitance			50	100	
t _{d(on)}	Turn-On Time ^{3,4}	V _{DD} =-50V, I _D =-5A, V _{GS} =-10V, R _G =25Ω		58	105	ns
t _r	Rise Time ^{3,4}			24	50	
t _{d(off)}	Turn-Off Time ^{3,4}			215	450	
t _f	Fall Time ^{3,4}			94	180	

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. V_{DD}=50V, V_{GS}=10V, L=0.1mH, I_{AS}=-60A., Starting T_J=25°C
3. The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%.
4. Essentially independent of operating temperature.

Typical Performance Characteristics




Fig.1 Continuous Drain Current vs. T_c




Fig.2 Normalized RDSON vs. T_j




Fig.3 Normalized V_{th} vs. T_j




Fig.4 Gate Charge Waveform




Fig.5 Normalized Transient Impedance




Fig.6 Maximum Safe Operation Area

Typical Performance Characteristics (Continue)




Fig.7 Switching Time Waveform





Fig.8 Gate Charge Waveform

Package Dimension

TO-252-2L









Dimensions				
SYMBOL	Millimeters		Inches	
	MIN	MAX	MIN	MAX
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
B	1.350	1.650	0.053	0.065
b	0.500	0.700	0.020	0.028
b1	0.700	0.900	0.028	0.035
C	0.430	0.580	0.017	0.023
C1	0.430	0.580	0.017	0.023
D	6.350	6.650	0.250	0.262
D1	5.200	5.400	0.205	0.213
E	5.400	5.700	0.213	0.224
e	2.300 TYP.		0.091 TYP.	
e1	4.500	4.700	0.177	0.185
L	9.500	9.900	0.374	0.390
L1	2.550	2.900	0.100	0.114
L2	1.400	1.780	0.055	0.070
L3	0.600	0.900	0.024	0.035
V	3.800 REF.		0.150 REF.	

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587