GSM1382NZF

100V N-Channel MOSFET

Product Description

The N-Channel enhancement mode power field effect transistor is using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode.

The device is well suited for high efficiency fast switching applications.

Features


- $R_{DS(ON)}$ = 8.2mΩ @ V_{GS}=10V
- $R_{DS(ON)}$ = 11mΩ @ V_{GS}=4.5V
- DFN3333A-8L Package
- RoHS Compliant and Halogen Free

Applications

- MB / VGA / Vcore
- POL Applications
- SMPS


Packages & Pin Assignments

DFN3333A-8L



Top View Bottom View

Equivalent Circuit



Pin	Symbol	Description	Pin	Symbol	Description
1	S	Source	**8**	D	Drain
2	S	Source	**7**	D	Drain
3	S	Source	**6**	D	Drain
4	G	Gate	**5**	D	Drain

Ordering and Marking Information

Ordering Information			
Part Number	**Package**	**Part Marking**	**Quantity / Reel**
GSM1382NZF	DFN3333A-8L	1382NZ □□□□□□	3,000 PCS

GSM1382 1 2

- **Product Code:** GSM1382
- **Package Code:** 1 is **NZ** for DFN3333A-8L
- **Green Level:** 2 is **F** for RoHS Compliant and Halogen Free

Marking Information



- **Product Code:** 1382NZ
- **GS Code:** □□□□□□

Absolute Maximum Ratings (T_A = 25ºC unless otherwise specified)

Symbol	Parameter		Value	Unit
V_{DSS}	Drain-Source Voltage		100	V
V_{GSS}	Gate-Source Voltage		±20	V
I_D	Continuous Drain Current (Silicon Limited)	T_C=25ºC	68	A
		T_C=100ºC	42	
	Continuous Drain Current (Package Limited)		50	
I_{DM}	Pulsed Drain Current [1]		160	A
I_{AS}	Single Pulse Avalanche Current, L = 0.1mH [1]		25	A
E_{AS}	Single Pulse Avalanche Energy, L = 0.1mH [1]		62.5	mJ
P_D	Power Dissipation	T_C=25ºC	78	W
		T_C=100ºC	31	
$R_{\theta JC}$	Thermal Resistance-Junction to Case		1.6	ºC/W
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient [2]		62	ºC/W
T_J	Operating Junction Temperature Range		-55 to +150	ºC
T_{STG}	Storage Temperature Range		-55 to +150	ºC

NOTE:
1. Single pulse width is limited by max junction temperature.
2. The device mounted on 1in^2 FR-4 board with 2oz. Copper

Electrical Characteristics (T_J = 25ºC unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=250μA	100	-	-	V
I_{DSS}	Drain-Source Leakage Current	V_{DS}=100V, V_{GS}=0V	-	-	1	μA
I_{GSS}	Gate-Source Leakage Current	V_{DS}=0V, V_{GS}=±20V	-	-	±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=250μA	1.2	-	2.5	V
$R_{DS(ON)}$	Drain-Source On-Resistance	V_{GS}=10V, I_D=20A	-	6.8	8.2	mΩ
		V_{GS}=4.5V, I_D=10A	-	8.9	11	
gfs	Forward Transconductance	V_{DS}=5V, I_D=20A	-	30	-	S
Dynamic Characteristics						
R_g	Gate Resistance	f=1MHz		1		Ω
C_{iss}	Input Capacitance	V_{DS}=50V, V_{GS}=0V, f=1MHz	-	2180	2980	pF
C_{oss}	Output Capacitance		-	550	-	
C_{rss}	Reverse Transfer Capacitance		-	13	-	
Q_g	Total Gate Charge	V_{DS}=50V, I_D=10A V_{GS}=10V	-	39	58	nC
Q_{gs}	Gate-Source Charge		-	4.4	-	
Q_{gd}	Gate-Drain Charge		-	12	-	
$t_{d(on)}$	Turn-On Delay Time	V_{DD}=50V, I_D=10A V_{GS}=10V, R_g=6Ω	-	14	-	ns
t_r	Turn-On Rise Time		-	21	-	
$t_{d(off)}$	Turn-Off Delay Time		-	34	-	
t_f	Turn-Off Fall Time		-	24	-	
Diode Characteristics						
V_{SD}	Diode Forward Voltage	V_{GS}=0V, I_S=1A	-	-	1	V
t_{rr}	Reverse Recovery Time	I_F=10A , dI/dt=100A/μs	-	67	-	ns
Q_{rr}	Reverse Recovery Charge		-	153	-	nC

Typical Performance Characteristics




FIG.1 Output Characteristics




FIG.2 Transfer Characteristics




FIG.3 On-Resistance vs. Gate Voltage




FIG.4 On-Resistance vs. Drain Current

Typical Performance Characteristics




FIG.5 Normalized On-Resistance vs. T_J




FIG.6 Normalized $V_{GS(th)}$ vs. T_J




FIG.7 Gate Charge Characteristics




FIG.8 Capacitance Characteristics

Typical Performance Characteristics




FIG.9 Diode Characteristics




FIG.10 Maximum Safe Operation Area






FIG.11 Normalized Transient Impedance

DFN333A-8L

Package Dimension



Recommended Land Pattern



Unit:mm

Dimensions				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	0.70	0.80	0.028	0.031
A1	0.00	0.05	0.000	0.002
b	0.24	0.35	0.009	0.014
c	0.15	0.25	0.006	0.010
D	3.20	3.40	0.126	0.134
D1	2.15	2.35	0.085	0.093
E	3.20	3.40	0.126	0.134
E1	2.13	2.33	0.084	0.092
E2	0.25	0.45	0.010	0.018
e	0.65 BSC		0.026 BSC	
L	0.30	0.50	0.012	0.020

NOTE:

1. Dimensions are exclusive of Burrs, Mold Flash and Tie Bar extrusions.

NOTICE

- Globaltech Semiconductor assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Globaltech Semiconductor products described or contained herein. Globaltech Semiconductor products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Globaltech Semiconductor makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

- Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F, NO.43-1, Lane 11, Sec. 6, Minquan E. Rd Neihu District, Taipei City 114761, Taiwan (R.O.C).
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587