

GSM6907Z

60V P-Channel MOSFETs

Product Description

These P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode.

These devices are well suited for high efficiency fast switching applications.


Features


- -60V, -14A, $R_{DS(ON)}=65m\Omega@V_{GS}=-10V$
- Fast switching
- Suit for -1.8V Gate Drive Applications
- Green Device Available
- Improved dv/dt capability

Applications


- Motor Drive
- Power Tools
- LED Lighting

Packages & Pin Assignments

GSM6907ZFF (DFN3X3-8L)	
 <p>Top View</p>	
Pin	Description
1	Source
2	Source
3	Source
4	Gate
5	Drain
6	Drain
7	Drain
8	Drain




Ordering Information



Part Number	Package	Quantity
GSM6907ZFF	DFN3X3-8L	5000pcs

Marking Information



Absolute Maximum Ratings

T_c=25°C Unless otherwise noted

Symbol	Parameter	Typical	Unit
V _{DS}	Drain-Source Voltage	-60	V
V _{GS}	Gate-Source Voltage	±20	V
I _D	Continuous Drain Current	T _c =25°C	-14
		T _c =100°C	-8.9
I _{DM}	Pulsed Drain Current ¹	-56	A
EAS	Single Pulse Avalanche Energy ²	31	mJ
IAS	Single Pulse Avalanche Current ²	-25	A
P _D	Power Dissipation (T _c =25°C)	33.8	W
	Power Dissipation-Derate above 25°C	0.27	W/°C
T _J	Operating Junction Temperature Range	-55 to +150	°C
T _{STG}	Storage Temperature Range	-55 to +150	°C
R _{θJA}	Thermal Resistance-Junction to Ambient	62	°C/W
R _{θJC}	Thermal Resistance-Junction to Case	3.7	°C/W

Electrical Characteristics

T_J=25°C Unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250uA	-60			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250uA	-1.2	-1.6	-2.2	
I _{GSS}	Gate-Source Leakage Current	V _{DS} =0V, V _{GS} =±20V			±100	nA
I _{DSS}	Drain-Source Leakage Current	V _{DS} =-60V, V _{GS} =0V			-1	uA
		V _{DS} =-48V, V _{GS} =0V T _J =125°C			-10	
I _S	Continuous Source Current	V _G =V _D =0V, Force Current			-14	A
I _{SM}	Pulsed Source Current				-28	A
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} = -10V, I _D = -8A		54	65	mΩ
		V _{GS} = -4.5V, I _D = -6A		70	90	
g _{FS}	Forward Transconductance	V _{DS} =-10V, I _D =-3A		7		S
V _{SD}	Diode Forward Voltage	I _S =-1A, V _{GS} =0V			-1	V
Dynamic						
Q _g	Total Gate Charge ^{3,4}	V _{DS} =-30V, V _{GS} =-10V, I _D =-3A		16.4	23	nC
Q _{gs}	Gate-Source Charge ^{3,4}			2.8	4	
Q _{gd}	Gate-Drain Charge ^{3,4}			3.6	6	
C _{iss}	Input Capacitance	V _{DS} =-30V, V _{GS} =0V, f=1MHz		870	1260	pF
C _{oss}	Output Capacitance			70	100	
C _{rss}	Reverse Transfer Capacitance			42	60	
t _{d(on)}	Turn-On Time ^{3,4}	V _{DD} =-30V, I _D =-1A, V _{GS} =-10V, R _G =6Ω		8.3	16	ns
t _r				29.6	56	
t _{d(off)}	Turn-Off Time ^{3,4}			51.7	98	
t _f				15.6	30	
R _g	Gate resistance		V _{GS} =0V, V _{DS} =0V, F=1MHz		16	

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. V_{DD}=-25V, V_{GS}=-10V, L=0.1mH, I_{AS}=-25A., R_G=25Ω, Starting T_J=25°C.
3. The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%.
4. Essentially independent of operating temperature.

Typical Performance Characteristics




Fig.1 Continuous Drain Current vs. T_c




Fig.2 Normalized $R_{DS(on)}$ vs. T_J




Fig.3 Normalized V_{th} vs. T_J




Fig.4 Gate Charge Waveform




Fig.5 Normalized Transient Impedance




Fig.6 Maximum Safe Operation Area

Typical Performance Characteristics (Continue)




Fig.7 Switching Time Waveform





Fig.8 EAS Waveform

Package Dimension

DFN3X3-8L







Dimensions



SYMBOL	Millimeters		Inches	
	MIN	MAX	MIN	MAX
A	0.700	0.800	0.028	0.031
b	0.250	0.350	0.010	0.013
c	0.100	0.250	0.004	0.009
D	3.250	3.450	0.128	0.135
D1	3.000	3.200	0.119	0.125
D2	1.780	1.980	0.070	0.077
D3	0.130 REF		0.005 REF	
E	3.200	3.400	0.126	0.133
E1	3.000	3.200	0.119	0.125
E2	2.390	2.590	0.094	0.102
e	0.650 BSC		0.026 BSC	
H	0.300	0.500	0.011	0.019
L	0.300	0.500	0.011	0.019
L1	0.130 REF		0.005 REF	
θ	0°	12°	0°	12°
M	0.150 REF		0.006 REF	

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587