

GSM6908D

60V N-Channel MOSFET

Product Description

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode.

These devices are well suited for high efficiency fast switching applications.



Features

- 60V, 27A, $R_{DS(ON)} = 28m\Omega @ V_{GS} = 10V$
- Improved dv/dt capability
- Fast switching
- Green Device Available
- 100% EAS Guaranteed


Applications

- Power Tools
- LED Lighting
- Motor Drive

Packages & Pin Assignments


GSM6908DF (TO-252-2L)	
 <p>Top View</p>	
Description	
Gate	
Drain	
Source	

Ordering Information



Part Number	Package	Quantity Reel
GSM6908DF	TO-252-2L	2500 PCS

Marking Information



Absolute Maximum Ratings

T_c=25°C Unless otherwise noted

Symbol	Parameter	Typical	Unit
V _{DS}	Drain-Source Voltage	60	V
V _{GS}	Gate-Source Voltage	±20	V
I _D	Continuous Drain Current	T _c =25°C	27
		T _c =100°C	17
I _{DM}	Pulsed Drain Current ¹	108	A
EAS	Single Pulse Avalanche Energy ²	26.5	mJ
IAS	Single Pulse Avalanche Current ²	23	A
P _D	Power Dissipation (T _c =25°C)	40	W
	Power Dissipation (Derate above 25°C)	0.32	W/°C
T _J	Operating Junction Temperature Range	-50 to +150	°C
T _{STG}	Storage Temperature Range	-50 to +150	°C
R _{θJA}	Thermal Resistance-Junction to Ambient	62	°C/W
R _{θJC}	Thermal Resistance-Junction to Case	3.1	°C/W

Electrical Characteristics

T_j=25°C Unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	60			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	1.2	1.7	2.5	V
I _{GSS}	Gate Leakage Current	V _{DS} =0V, V _{GS} =±20V			±100	nA
I _{DSS}	Drain-Source Leakage Current	V _{DS} =60V, V _{GS} =0V, T _J =25°C			1	uA
		V _{DS} =48V, V _{GS} =0V, T _J =125°C			10	
I _S	Continuous Source Current	V _G =V _D =0V, Force Current			27	A
I _{SM}	Pulsed Source Current				54	
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} =10V, I _D =15A		23	28	mΩ
		V _{GS} =4.5V, I _D =10A		27	34	
g _{FS}	Forward Transconductance	V _{DS} =10V, I _D =8A		11		S
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _S =1A, T _J =25°C			1	V
Dynamic						
Q _g	Total Gate Charge ^{2,3}	V _{DS} =30V, V _{GS} =10V, I _D =10A		16.4	32	nC
Q _{gs}	Gate-Source Charge ^{2,3}			3.1	6	
Q _{gd}	Gate-Drain Charge ^{2,3}			3.7	7	
C _{iss}	Input Capacitance	V _{DS} =30V, V _{GS} =0V, F=1MHz		1180	2200	pF
C _{oss}	Output Capacitance			80	160	
C _{rss}	Reverse Transfer Capacitance			52	100	
t _{d(on)}	Turn-On Time ^{2,3}	V _{DD} =30V, I _D =1A, V _{GS} =10V, R _G =6Ω		4.6	9	ns
t _r				14.8	28	
t _{d(off)}	Turn-Off Time ^{2,3}			27.2	52	
t _f				7.8	15	
R _g	Gate Resistance		V _{DS} =0V, V _{GS} =0V, F=1MHz		1.3	

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. V_{DD}=50V, V_{GS}=10V, L=0.1mH, I_{AS}=23A., R_G=25Ω, Starting T_J=25°C
3. The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%.
4. Essentially independent of operating temperature.

Typical Performance Characteristics




Fig.1 Continuous Drain Current vs. T_c




Fig.2 Normalized R_{DS(on)} vs. T_j




Fig.3 Normalized V_{th} vs. T_j




Fig.4 Gate Charge Waveform




Fig.5 Typical Output Characteristics




Fig.6 Turn-On Resistance vs. I_D

Typical Performance Characteristics (Continue)




Fig.7 Capacitance Characteristics




Fig.8 Normalized Transient Impedance




Fig.9 Maximum Safe Operation Area




Fig.10 Switching Time Waveform





Fig.11 EAS Waveform

Package Dimension

TO-252-2L









Dimensions				
SYMBOL	Millimeters		Inches	
	MIN	MAX	MIN	MAX
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
B	1.350	1.650	0.053	0.065
b	0.500	0.700	0.020	0.028
b1	0.700	0.900	0.028	0.035
C	0.430	0.580	0.017	0.023
C1	0.430	0.580	0.017	0.023
D	6.350	6.650	0.250	0.262
D1	5.200	5.400	0.205	0.213
E	5.400	5.700	0.213	0.224
e	2.300 TYP.		0.091 TYP.	
e1	4.500	4.700	0.177	0.185
L	9.500	9.900	0.374	0.390
L1	2.550	2.900	0.100	0.114
L2	1.400	1.780	0.055	0.070
L3	0.600	0.900	0.024	0.035
V	3.800 REF.		0.150 REF.	

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587