

GSMBSS139Y

Dual N-Channel Enhancement MOSFET

Product Description

These Dual N-Channel Enhancement Mode Power Field Effect Transistors are Using Trench DMOS Technology. This Advanced Technology has been Especially Tailored to Minimize on-state Resistance, Provide Superior Switching Performance, and Withstand high Energy Pulse in the Avalanche and Commutation mode.

These Devices are well Suited for High Efficiency Fast Switching Applications.


Features

- 60V, 0.2A, $R_{DS(ON)}=2.5\Omega@V_{GS}=4.5V$
- Improved dv/dt Capability
- Fast Switching
- Green Device Available
- SOT-563 Package Design
- ESD Protected : 1500V


Applications

- Notebook
- Load Switch
- LED Applications

Packages & Pin Assignments




Ordering Information



Part Number	Package	Quantity
GSMBSS139YX7F	SOT-563	3000pcs

Marking Information



Part Number	Package	Part Marking
GSMBSS139YX7F	SOT-563	J2WM

Absolute Maximum Ratings

T_A=25°C Unless otherwise noted

Symbol	Parameter	Limits	Unit
V _{DS}	Drain-Source Voltage	60	V
V _{GS}	Gate-Source Voltage	±20	V
I _D	Continuous Drain Current T _A =25°C	0.2	A
I _{DM}	Pulsed Drain Current	0.8	A
P _D	Power Dissipation (T _A =25°C)	0.225	W
	Power Dissipation (Derate above 25°C)	0.0018	W/°C
T _J	Operating Junction Temperature Range	-55 to +150	°C
T _{STG}	Storage Temperature Range	-55 to +150	°C
R _{θJA}	Thermal Resistance-Junction to Ambient	556	°C/W
TL	Maximum Lead Temperature for Soldering Purpose, for 10 Seconds	260	°C





Electrical Characteristics

T_A=25°C Unless otherwise noted






Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	60	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	0.85	-	1.45	V
I _{GSSF}	Gate Leakage Current , Forward	V _{DS} =0V, V _{GS} =20V			10	μA
I _{GSSR}	Gate Leakage Current , Reverse	V _{DS} =0V, V _{GS} =-20V			-10	μA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =25V, V _{GS} =0V			0.1	uA
		V _{DS} =50V, V _{GS} =0V,			0.5	
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} =4.5V, I _D =0.2A		-	2.25	Ω
		V _{GS} =2.5V, I _D =0.1A	-	-	4.05	
g _{FS}	Forward Transconductance	V _{DS} =25V, I _D =0.2A	100	-	-	mS

Dynamic						
C _{iss}	Input Capacitance	V _{DS} =25V, V _{GS} =0V, f=1MHz		22.8		pF
C _{oss}	Output Capacitance			3.5		
C _{rss}	Reverse Transfer Capacitance			2.9		
t _{d(on)}	Turn-On Time	V _{DD} =30V, I _D =1A, V _{GS} =10V, R _G =25Ω		3.8		ns
t _{d(off)}	Turn-Off Time			19		

Typical Performance Characteristics




Typical Performance Characteristics (Continue)



Package Dimension

SOT-563



Dimensions				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	0.500	0.600	0.020	0.024
b	0.150	0.300	0.006	0.012
c	0.080	0.160	0.003	0.006
D	1.500	1.700	0.059	0.067
E	1.100	1.300	0.043	0.051
E1	1.500	1.700	0.059	0.067
e	0.5(BSC)		0.02(BSC)	
L	0.100	0.300	0.004	0.012

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd NeiHu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587