

GSMBSS84

60V P-Channel Enhancement Mode MOSFET

Product Description

GSMBSS84, P-Channel enhancement mode MOSFET, uses Advanced Trench Technology to provide excellent $R_{DS(ON)}$, low gate charge.

These devices are particularly suited for low voltage power management, such as smart phone and notebook computer and other battery powered circuits, and low in-line power loss are needed in commercial industrial surface mount applications.


Features

- -60V/-0.13A, $R_{DS(ON)}=10\Omega@V_{GS}=-5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability
- SOT-23 package design


Applications

- DC to DC Converter
- Cellular & PCMCIA Card
- Cordless Telephone
- Power Management in Portable and Battery etc.

Packages & Pin Assignments




Ordering Information



Part Number	Package	Quantity
GSMBSS84JZF	SOT-23	3000 PCS

Marking Information



Absolute Maximum Ratings

($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Typical	Unit
V_{DSS}	Drain-Source Voltage	-60	V
V_{GSS}	Gate-Source Voltage	± 20	V
I_D	Continuous Drain Current ($T_A=25^{\circ}\text{C}$)	-130	mA
I_{DM}	Pulsed Drain Current ($t_p \leq 10\mu\text{s}$)	-520	mA
I_S	Continuous Current	-0.13	A
P_D	Power Dissipation ($T_A=25^{\circ}\text{C}$)	225	mW
T_J	Operating Junction Temperature	-55 to 150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^{\circ}\text{C}$
$R_{\theta JA}$	Maximax Junction to Ambient	556	$^{\circ}\text{C}/\text{W}$

Note 1: Pulse Test: $PW \leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.


Note 2: Switching Time is Essentially Independent of Operating Temperature.

Electrical Characteristics


($T_A=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=-250\mu A$	-60			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=-1.0mA$	-0.8		-2.0	V
I_{GSS}	Gate-Source Leakage Current	$V_{DS}=0V, V_{GS}=\pm 20V$			± 60	μA
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=-25V, V_{GS}=0V$			-0.1	μA
		$V_{DS}=-50V, V_{GS}=0V$			-15	
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=-5V, I_D=-100mA$			10	Ω
g_{fs}	Forward Transconductance	$V_{DS}=-25V, I_D=-100mA, f=1.0KHz$	50			mS
V_{SD}	Forward Voltage			-2.5		V
Dynamic						
C_{iss}	Input Capacitance	$V_{DS}=-5V, V_{GS}=0V, f=1MHz$		30		μF
C_{oss}	Output Capacitance			10		
C_{rss}	Reverse Transfer Capacitance			5.0		
Q_G	Gate Charge			6		nC
$t_{d(on)}$	Turn-On Time	$V_{DD}=-15V, R_L=50\Omega, I_D=-2.5A$		25		ns
t_r				1.0		
$t_{d(off)}$	Turn-Off Time			16		
t_f				8.0		

Typical Performance Characteristics




Transfer Characteristics




On-Region Characteristics


Typical Performance Characteristics (continue)




On-Resistance versus Drain Current




On-Resistance versus Drain Current



On-Resistance Variation with Temperature




Gate Charge



Body Diode Forward Voltage

Package Dimension

SOT-23







Dimensions



SYMBOL	Millimeters		Inches	
	MIN	MAX	MIN	MAX
A	0.75	1.17	0.030	0.046
A1	0.05	0.15	0.002	0.006
A2	0.70	1.02	0.028	0.040
b	0.30	0.50	0.012	0.020
c	0.08	0.20	0.003	0.008
D	2.80	3.04	0.110	0.120
E	2.10	2.64	0.083	0.104
E1	1.20	1.40	0.047	0.055
e	0.95 (TYP)		0.037 (TYP)	
e1	1.90 (TYP)		0.075 (TYP)	
L	0.40	0.60	0.016	0.024
L1	0.54 (TYP)		0.021 (TYP)	
G	0.25 (TYP)		0.010 (TYP)	
θ	0°	8°	0°	8°

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587